



SIGMA+

Superior Performance on Any Surface

WITH HP INKJET TECHNOLOGY



NON-CMR, PFAS-FREE

SIGMA+ is a solvent black ink for HP45si technology formulated to have the highest level of durability and adhesion, producing dark and crisp impressions across a wide range of substrates while maintaining the exceptionally long decap time of the SIGMA family of inks.

HEADQUARTERS



SIGMA+ | TSK3646

Technical Specifications	
Ink Type	Solvent
Color	Black
Colorant	Dye
Firing Parameters	Voltage: 9.0V Pulse Width: 1.8 μ s
Pulse Warning	Off
Open Time	~ 16 hrs
Shelf Life	TBD
Bulk Use	Suitable
Storage Conditions	10°C ~ 30°C
Operating Conditions	10°C ~ 40°C; >30% RH
Maintenance	Gently wipe printhead with a dry, lintfree cloth
Downtime	<p>< 1 day down; leave cartridges in machine, wipe/purge before next use</p> <p>> 1 day down: remove cartridge from machine and seal with cartridge clip, wipe/purge next use</p>

Note: Performance results dependant on individual application parameters, e.g. substrate environment print orientation.

Performance Data	
Optical Density	████████████████████
Dry Time	████████████████████
Substrate Adhesion	████████████████████
Substrate Wetting	████████████████████
Decap Time	████████████████████

For Non-porous Media	
OPP	PP
PET	PE
AL	BLISTER FOIL
RUBBER	GLASS
AQUEOUS VARNISH COAT	
GRAVURE PRINT SURFACE	PAPER

Application Example	
O.D 100% Coverage Bar	2.52
Dry Time Size 12 Arial Text	< 3s

600x300DPI, Aluminum Foil



Regulatory Compliance			
EuPIA	REACH SVHC	Non-CMR	PFAS Free



HEADQUARTERS

1201 Edison Drive
Cincinnati, OH 45216
+1 513 948 9000

E: info@kaocollins.com | www.kaocollins.com